



MobileCollect Wireless
USB MicroBase Receiver
 Part #: MC-BASE-MICRO

Features

- For mobile data collection using laptops or tablets
- Supports all MobileCollect Wireless transmitter models
- Supports U-Wave-T, TC, & TM transmitter models
- Supports CDI CORE & VRS “Long-Range” indicators
- Data transfer via USB serial connection to computer
- Power provided by USB computer connection
- Range up to 133 feet / 40 meters
- Status LEDs
- Field upgradable firmware
- Made in the USA

Specifications

Size	1.79" x 0.79" x 0.42" (L x W x H)	Baud Rates	9600 - 19.2K - 38.4K baud
Weight	0.30 oz	LED Status Indicators	Power On Wireless Data Packet Received Receive Command from PC
Range	Up to 133' line of site indoors	Output Format	Multiple output options, configured via Windows PC setup program
Power Requirements	5VDC power from computer USB port	Frequency	2.4 GHz (2.4000 to 2.4835) ISM band (Industrial, Scientific, & Medical)
PC Connection	RS-232 serial via USB port	Operating Temperature & Humidity	32° to 122° F 90% humidity; non-condensing
Read Switch Connectors	None	Certifications	FCC, IC, CE, RoHS, REACH

USB Serial Connector



LED Status Indicators