

MobileCollectTM

RF Sniffer

User's Guide

MobileCollect RF Channel Sniffer Program

Copyright © 2010-2017 Microridge Systems, Inc.

All rights reserved. No parts of this work may be reproduced in any form or by any means - graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems - without the written permission of the publisher.

Products that are referred to in this document may be either trademarks and/or registered trademarks of the respective owners. The publisher and the author make no claim to these trademarks.

While every precaution has been taken in the preparation of this document, the publisher and the author assume no responsibility for errors or omissions, or for damages resulting from the use of information contained in this document or from the use of programs and source code that may accompany it. In no event shall the publisher and the author be liable for any loss of profit or any other commercial damage caused or alleged to have been caused directly or indirectly by this document.

Printed: Friday, March 31, 2017 at 11:22 AM in Sunriver, Oregon.

Table of Contents

Chapter 1 MobileCollect RF Channel Sniffer.....	1
Chapter 2 Contact MicroRidge.....	5

1 MobileCollect RF Channel Sniffer

The MobileCollect RF Channel Sniffer allows you to determine the amount of RF communications occurring on each of the RF channels that can be used by MobileCollect wireless. The Sniffer takes 500 measurements on a channel and determines for each measurement if there was any RF activity. After the measurements are taken on a channel, the Sniffer moves to the next channel and repeats the process. It takes approximately .096 seconds (96 msec) to capture the 500 measurements on a channel. The total time to scan all 16 channels is about 1.6 seconds.

The screenshot shows the 'MobileCollect RF Channel Sniffer -- COM9 @ 9600-N-8-1' window. It features a main data table with columns for Channel, Frequency Midpoint (GHz), Total Meas, Sample Periods, Total Time (hr:min:sec), Active Time (hr:min:sec), Active Time Percent, and a detailed breakdown of 'Total Time for Each Channel Utilization Range, hr:min:sec or seconds'. The utilization ranges are: 0.0 to 1.0 %, 1.1 to 3.0 %, 3.1 to 5.0 %, 5.1 to 10.0 %, 10.1 to 25.0 %, 25.1 to 50.0 %, 50.1 to 75.0 %, and 75.1 to 100.0 %.

Summary information:

- Avg sample size = 500.0 measurements
- Avg sample period = .0919 seconds
- Test start date = 10-22-2013
- Test start time = 6:29:10 AM
- Test duration = 1:11:04 hr:min:sec

Color codes:

- Blue = Last channel updated
- Light Blue = Last cell modified for channel
- Green = Excellent channel for MobileCollect
- Yellow = Acceptable channel for MobileCollect

Time formats:

Several time formats are used to display the time intervals. These consists of hours:minutes:seconds (1:45:15), minutes:seconds (12:03) and seconds (1.3 sec). The seconds format is only used for time intervals less than 2.0 seconds.

Buttons: About, Print, Serial Port, Help, Start, Clear, Close.

MobileCollect Sniffer is only compatible with the following base units:

- MobileCollect USB Base
- MobileCollect MicroBase
- MobileCollect RS-232 Base

MobileCollect wireless operates in the 2.45 GHz Industrial, Scientific and Medical (ISM) radio band. This frequency is also used by other wireless equipment such as WiFi. If you are not using other 2.45 GHz equipment in your facility, you would not need to use the Sniffer to determine the best channels to use. However, if you have other wireless systems operating in the 2.45 GHz band, it is a good idea to run the Sniffer to determine the activity levels on the available channels.

Operation

In order to use the Sniffer, you must have a MobileCollect USB Base, RS-232 Base or MicroBase connected to your PC. You also need to specify the serial port that the base unit is connected to. The Sniffer will automatically determine the baud rate required by the base unit. After selecting the appropriate serial port, press the Start button to begin the Sniffer test.

The Sniffer test should run for hours, not minutes. If the time period that you will be using MobileCollect runs from 7:00 AM to 4:00 PM, your Sniffer test should be run during that time period. If you are not using MobileCollect from 4:00 PM to 7:00 AM, any information collected by the Sniffer during the 4:00 PM to 7:00 AM time period is useless in determining channel availability.

You cannot save the data collected by the Sniffer. However, a one page printed report can be generated by pressing the print button. All printing should be done in landscape mode.

Time Formats

The times are displayed in 3 different formats. Pay close attention to these formats so you do not misinterpret the times being displayed.

hr:min:sec	This format is used when the time being displayed is greater than 1 hour.
min:sec	This format is used for times less than 1 hour and greater than 2 seconds
sec	When the total time is less than 2 seconds, the number of seconds are displayed with 1 decimal place (i.e. 1.3 sec). When the time is 2 seconds or greater, the min:sec format is used. When this seconds format is used, the word sec always appears after the time.

Grid Columns

Channel	The MobileCollect channel number. The channel number for WiFi equipment is different from this channel numbering.
Frequency Midpoint	The midpoint frequency for each channel. The frequency range for each channel is 0.0030 GHz. The minimum and maximum frequency for each channel is 0.0015 GHz below and 0.0015 GHz above the frequency midpoint. The frequency range for each channel is smaller than the channel frequency range used by WiFi.
Total Meas	The total number of measurements for each channel. If you run the Sniffer 8 hours, each channel will have about 9,000,000 measurements.
Sample Periods	The total number of sample periods for each channel. If you run the Sniffer 8 hours, each channel will have about 18,000 sample periods.

Total Time	The total time each channel was monitored during the test. If you run the Sniffer 8 hours, the total sample time for each channel will be about 30 minutes.
Active Time	The total time that activity was observed for a channel.
Active Time, Percent	The percentage of the time that a channel had RF activity while it was being monitored. This value is used to flag the Excellent and Acceptable MobileCollect channels.
0 to 1.0%	The amount of time that RF activity was observed for this utilization range. The utilization range for this item is 0 to 1.0%. When data for a sample period is received by the Sniffer, the percent utilization is calculated (total measurements with RF activity / total measurements). If this calculation ranges from 0 to 1.0%, the time of the sample period is added to the total for the channel being analyzed. Larger times for this utilization range indicates very little RF activity for the channel.
1.1 to 3.0%	See explanation above. Times for this utilization range indicate a low amount of RF activity for a channel.
3.1 to 5.0%	See explanation above. Times for this utilization range indicate a low amount of RF activity for a channel.
5.1 to 10.0%	See explanation above. Times for this utilization range indicate a low amount of RF activity for a channel.
10.1 to 25%	See explanation above. Times for this utilization range indicate a moderate amount of RF activity for a channel.
25.1 to 50%	See explanation above. Times for this utilization range indicate a moderate amount of RF activity for a channel.
50.1 to 75%	See explanation above. Times for this utilization range indicate a high amount of RF activity for a channel.
75.1 to 100%	See explanation above. Times for this utilization range indicate a high amount of RF activity for a channel.

Excellent & Acceptable Channels

To assist in identifying channels to use for MobileCollect, Excellent and Acceptable channels are marked with a light green or light yellow color. Even if a channel is marked as Excellent or Acceptable, you should still take a close look at the time in each of the utilization ranges.

You could have a channel that has virtually no activity most of the time; however, when there is activity, all of the activity is in the 75.1 to 100% utilization range. This channel may experience some measurement problems if you are taking measurements when the channel activity is very high.

MobileCollect Channels

The following MobileCollect products can utilize channels 11 to 26.

- USB Base
- RS-232 Base
- MicroBase
- Digital Mobile Module
- Command Mobile Module
- Mini Mobile Module
- RS-232 Mobile Module (V2)

The default channel for MobileCollect is 21. Channel 14 is reserved for firmware updates and Mobile Module setup.

2 Contact MicroRidge

Email:

Support: support@microridge.com
Sales: sales@microridge.com
Information: info@microridge.com

Phone:

Support: 541.593.1656
Sales: 541.593.3500
Main office: 541.593.1656
Fax: 541.593.5652

Mailing Address:

MicroRidge Systems, Inc.
PO Box 3249
Sunriver, OR 97707-0249

Shipping Address:

MicroRidge Systems, Inc.
56888 Enterprise Drive
Sunriver, OR 97707

Note: There is no mail delivery to this address. This address should only be used for UPS and FedEx package delivery services.

Web: www.microridge.com